BPWX 4 Series

4 Watt Power Supply Single (Vo) or Dual (Vo & Vr) output BPWX 4-08-00, -08-33, -08-50 BPWX 4-14-00, -14-33, -14-50 BPWX 4-24-00

The BPWX Power Supply Module is the ideal low EMI solution for worldwide deployment of control applications in wireless/ M2M, lighting, sensing, smart building and power distribution, especially where long range wireless operation or extended temperature is required.

A patented design incorporating a custom integrated circuit into a small package (2.45 in³ [40.1 cm³]) the BIAS Module provides an immediate "drop-in" solution, requiring no additional external components.

Operating Specifications

(@120VAC / 60 Hz / 25°C unless otherwise specified)

Electrical	
Input Voltage Range	90 - 308 VAC (50/60Hz)
Input Surge Withstand	345V, < 30 sec
Output Power (Pmax)	4 W min. (60Hz) 3.33 W min. (50Hz)
Efficiency	≥ 70%
Output Vo (Peak)	8, 14 or 24 VDC nom. +/- 5%
Line / Load Regulation Vo (Peak)	+/- 1% Po < Pmax
Temperature Regulation Vo (Peak)	+/- 2% Po < Pmax
Ripple Vo (@120 Hz) (@ 100 kHz)	1.75 V p:p 0.25 V p:p
Output Vr, 3.3 volt (+/- 5%)	For Vo = 8V, Ir out 160mA max, Io+Ir \leq 500mA For Vo = 14V, Ir out 70mA max, Io+Ir \leq 285mA For Vo = 24V, Vr not available
Output Vr, 5.0 volt (+/- 5%)	For Vo = 8V, Ir out 250mA max, Io+Ir \leq 500mA For Vo = 14V, Ir out 83mA max, Io+Ir \leq 285mA For Vo = 24V, Vr not available
No-load Consumption	30 mW typical @ Vin=120 VAC
Isolation	3000 VAC (meets UL / CSA & EN Product Safe- ty)
Earth Leakage @ 120 VAC	< 10 uA
Short Circuit Protection	Continuous, Pin ≤ 0.7 w @ Vin = 120 VAC
Reliability @ 25° C, MIL HDBK-217F	> 500 Khr MTBF
Thermal	
Operating Temperature	-40 to +85° C
Operating Relative Humidity	0 – 95%, non-condensing
Storage Temperature	-40 to +105º C
Mechanical	
Package Size (L x W x H)	1.91 x 1.31 x 0.98 inches [48.5 x 33.3 x 24.9 mm]
Safety	
Safety Compliance	IEC 62368-1:2014 (CB Report Available)
EMI Emissions	EN 55022, Class B, FCC Part 15, Class B





c**SV**us

Features:

- Extended Temperature with NO DE-RATING! (-40 to +85°C)
- Universal Input (90-308 VAC, 50/60Hz)
- Small Size—2.45 in³ [40.1 cm³]
- Low no-load input power <30mW
- Constant power mode (not current limit)
- 3000 VAC Isolation
- EN 55022, Class B; FCC Part 15, Class B
- IEC 62368-1:2014

Bias Power AC/DC power supplies are available with two different types of outputs to fit your applications...

The characteristics of the main (Vo) and auxiliary (Vr) outputs are different and each has application-specific benefits which can provide high value to the system designer:

Vo is a voltage-regulated output which has a constant power mode instead of a conventional current limit. This output is best suited as a source for isolated DC utility power, which may be used directly or post-regulated with either a linear regulator or a DC/DC converter. **Vo is self protecting, cannot be overloaded and can be shorted indefinitely.** So unlike design-yourown, or partially complete modules where significant design margin is required to stay far away from current limit, **there is no need to oversize a Bias Power supply.** The graceful transition from voltage regulation to constant power along with the wide range of product ratings allows the designer to select a supply tightly matched to the design load.

Vr is also a voltage-regulated output and is thermally protected from overload. It has very low output ripple capable of driving elements which require a low-noise, tightly-regulated supply. In addition, Vr is supplied internally by Vo. This means that any capacitance added to Vo can increase the hold-up time of Vr as well.

*Note: maximum currents specified for constant voltage range only. See V-I curve on page 2 for Vo in constant power range.



BPWX 4 Series Data Sheet, Page 1 of 2 Revised 4/27/2021 Specifications subject to change

BPWX 4 Series

4 Watt Power Supply Single (Vo) or Dual (Vo & Vr) output BPWX 4-08-00, -08-33, -08-50 BPWX 4-14-00, -14-33, -14-50 BPWX 4-24-00

Part Number Designation

Part Number	Output Configuration	Vo	Vr
BPWX 4-08-00	Single output	8 VDC	N/A
BPWX 4-08-33	Dual Output	8 VDC	3.3 VDC
BPWX 4-08-50	Dual Output	8 VDC	5.0 VDC
BPWX 4-14-00	Single output	14 VDC	N/A
BPWX 4-14-33	Dual Output	14 VDC	3.3 VDC
BPWX 4-14-50	Dual Output	14 VDC	5.0 VDC
BPWX 4-24-00	Single Output	24 VDC	N/A





PIN	DESCRIPTION	
L1	Input High	
L2	Input Low	
N/C	No Connection	
Vo	Output	
GND	Ground	
Vr	Vr Output	
N/C	No Connection	
<u>NOTES</u> 1. Pins 0.031" [0.787 mm] round		
2. Pins extend	Pins extend 0.125" [3.175 mm]	

below stand-offs

Recommended Isolation, Isolation Spacing Primary





[48.5] 1.91



[24.9] 0.98 [33.3] 1.31

> BPWX 4 Series Data Sheet, Page 2 of 2 Revised 4/27/2021 Specifications subject to change

www.citapower.com

[3.175] 0.125